





# SURBITON



## Recommended Installation Method



Ashlar

[www.enviratile.com.au](http://www.enviratile.com.au)

## Specifications

<b>Construction</b>	Multi Level Tufted Loop Pile
<b>Face fibre</b>	100% Sunylon recycled nylon BCF
<b>Dye method</b>	100% Solution dyed
<b>Tufting gauge</b>	1/10"
<b>Pile weight</b>	745 g/m <sup>2</sup> (22 oz/sq.yd)
<b>Pile height</b>	4mm
<b>Backing material</b>	EnviraSoft™ A cushion back
<b>Backing thickness</b>	4mm
<b>Tile size</b>	50cm X 50cm (9.5mm overall thickness)

## Performance

<b>Electrostatic properties</b>	CNS 13595 10≤2.0kV 20% R.H. 70°F
<b>Flammability</b>	BS 4790: Hot Metal Nut, Method 1 Pass
<b>Radiant Heat Source</b>	AS ISO 9239.1.2003.CHF 5.2 kW/m <sup>2</sup>
<b>Wear Classification</b>	Contract Extra Heavy Duty + Stairs

## Acoustic Behaviour (EnviraSoft™)

<b>Sound absorption</b>	EN ISO 354 and EN ISO 11654
<b>Average coefficient (α<sub>w</sub>)</b>	0.41 (H)